

# Vortex impeller



# 80UYZ

3-phase  
50Hz


## Specifications:

Model		Colour code curve	Bore mm	Power output kW	Phases	r.p.m.	Head max. m	Capacity max. l/min	Starting method	Dry weight kg without cable		Impeller passage mm
free standing	with guide rail fitting									free standing	with guide rail fitting	
80UYZ42.6	TOS80UYZ42.6	1	80	2,6	3	1450	12,8	1548	direct	86,3	71,0	80


3.7 kW version available in d.o.l. or star-delta



ø Discharge bore mm		80mm	
Pumping Fluid	Temperature	0-40°C	
	Type of Fluid	Municipal sewage	
Pump	Components	Impeller	Vortex impeller
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Impeller	Grey iron casting EN-GJL-250
		Casing	Grey iron casting EN-GJL-250
		Shaft Seal	SiC, upper in oil bath
Wearing	Bronze		
Motor	Type, Poles		Induction motor, 4 poles, IP68
	Lubrication		Turbine oil (ISO VG32)
	Insulation		Insulation class H
	Motor Protector (built-in)		Miniature protector
	Phase / Voltage		3-phase / 400V / 50Hz / d.o.l.
	Material	Casing	Grey iron casting EN-GJL-250
		Shaft	Stainless steel EN-X5CrNiMo17-12-2
Cable		Rubber, 10m H07RN8-F	
Discharge Connection		Flange DIN/ANSI DN80 (PN10)	
Optional Accessories		Guide rail fitting "TOS" (guide support, duck foot bend, lifting chain) / Bend and stand set for free standing types	



Model	A	B	B1	C	C1	DN1	DN2	DN3	F1	F2	F3	G	H	J1
80UYZ42.6	563	408	250	316	158	80	100	3"	125	203	301	395	628	137



W1: lowest running water level